



IP66 Waterproof LED Street Light

With an IP66 waterproof rating, it is resistant to harsh weather conditions, ensuring its durability and reliability. Three different light effects can be chosen, namely 130 lm/w, 150 lm/w or 170 lm/w.



Smart Control Switch



Timed off



Intelligent light control



IP66 waterproof grade

Potenza:	50 W
Tensione di Alimentazione:	220-240V AC
Multitensione:	100-240V AC
Freq. di Funzionamento:	50-60 Hz
Classe Isolamento Elettrico:	II
Dimmerabile:	DALI
Fonte Luminosa:	SMD5050
Flusso Luminoso:	8400 lm
Rendimento LED:	170 lm/W
Efficienza energetica 2023 (UE-2019/2015):	C
Tipo di Lente:	60°/90°/ 120°/T2 M/T3M/ T4M Asimmetrico
Uso:	Esterno
Protezione IP:	IP66
Protezione IK:	IK09
Materiale del Corpo:	Alluminio, PMMA
Dimensioni:	568x200x109 mm
Durata:	80.000 Ore



IP66 Waterproof LED Street Light

With an IP66 waterproof rating, it is resistant to harsh weather conditions, ensuring its durability and reliability. Three different light effects can be chosen, namely 130 lm/w, 150 lm/w or 170 lm/w.



Smart Control Switch



Timed off



Intelligent light control



IP66 waterproof grade

Potenza:	75 W
Tensione di Alimentazione:	220-240V AC
Multitensione:	100-240V AC
Freq. di Funzionamento:	50-60 Hz
Classe Isolamento Elettrico:	II
Dimmerabile:	DALI
Fonte Luminosa:	SMD5050
Flusso Luminoso:	12750 lm
Rendimento LED:	170 lm/W
Efficienza energetica 2023 (UE-2019/2015):	C
Tipo di Lente:	60°/90°/ 120°/T2 M/T3M/ T4M Asimmetrico
Uso:	Esterno
Protezione IP:	IP66
Protezione IK:	IK09
Materiale del Corpo:	Alluminio, PMMA
Dimensioni:	568x200x109 mm
Durata:	80.000 Ore



IP66 Waterproof LED Street Light

With an IP66 waterproof rating, it is resistant to harsh weather conditions, ensuring its durability and reliability. Three different light effects can be chosen, namely 130 lm/w, 150 lm/w or 170 lm/w.



Smart Control Switch



Timed off



Intelligent light control



IP66 waterproof grade

Potenza:	100 W
Tensione di Alimentazione:	220-240V AC
Multitensione:	100-240V AC
Freq. di Funzionamento:	50-60 Hz
Classe Isolamento Elettrico:	II
Dimmerabile:	DALI
Fonte Luminosa:	SMD5050
Flusso Luminoso:	17000 lm
Rendimento LED:	170 lm/W
Efficienza energetica 2023 (UE-2019/2015):	C
Tipo di Lente:	60°/90°/ 120°/T2 M/T3M/ T4M Asimmetrico
Uso:	Esterno
Protezione IP:	IP66
Protezione IK:	IK09
Materiale del Corpo:	Alluminio, PMMA
Dimensioni:	613x240x109 mm
Durata:	80.000 Ore